

Touch Lamina

Wireless touch switch plate



Product Overview

Specifications

Input	3V (2 x CR2032 batteries) / AC
Operating Temperature	0 °C ~ 40 °C 10% ~90% RH
Storage Temperature	-10 °C ~ -70 °C 5% ~90% RH
Pairing	<ul style="list-style-type: none"> • Silux Control® network • Direct connect
Network	Silux Control® RF proprietary encrypted
RF Range	50m open air & meshing
Radio Frequency	868MHZ (Adjustable frequency to meet different county legislations)
Encryption	Silux Control® RF proprietary meshing
Language	English, others coming soon
OS	Android 4.0+, iOS 8.0+, Windows 7+
App Software	Silux Control® can be integrated with other automation features of Silux Control®

The Touch Lamina® is an alternative way for you to control any device connected to the Silux Control® network.

You can replace your current switches or use it as an addition to them.

With the added bonus of being wireless, you save on wiring installation costs. The Touch Lamina® can easily be placed where most convenient.

Features:

- UK/USA available in 2 or 4 buttons
- Program any button to dim lights or switch devices such as air conditioning, lighting, plug points and swimming pool pumps etc. on and off
- Install wireless - save money and time

Note: Can be used without the need of an IntelliHub® by being programmed as direct connect with the Collector®

